

spirit of excellence




## Pulvis 60<sup>†</sup>

60 W Thulium Fiber Laser (TFL)



## 60 W Thulium Fiber Laser (TFL)







The Pulvis 60+ is a Thulium Fiber Laser (TFL) which can be used for both, lithotripsy and for precise soft tissue surgery. Over the last few years, TFL technology has emerged as a new alternative to Holmium Lasers. As well as being particularly suitable for the treatment of stones, it also produces effective results when used in the Endoscopic Enucleation of the Prostate (EEP).

**Pulvis 60**+ – coming soon to your operating room!

## The advantages at a glance

- Reduced energy consumption High output with lower energy consumption
- Effective lithotripsy Full power output even with 200 µm fibers
- Effective enucleation "Low-power" ThuLEP with max. 60 W possible
- Compatible with standard wall sockets No high-voltage current supply required
- Minimized retropulsion when ablating the stone
- Continuous and pulsed emission "Traditional" ThuLEP and "super-pulsed" ThuLEP possible
- Effective hemostasis High degree of absorption of laser radiation
- Disposable and reusable fibers from 150 µm to 1,000 µm
- Very high-frequency emission up to 2,500 Hz
- Compact design Saves space in the operating room

## Technical data

| Laser classification       | Class 4 – thulium fiber laser             |
|----------------------------|---|
| Maximum peak output        | 500 W                                     |
| Wavelength                 | 1,920 – 1,960 nm                          |
| Laser energy               | 0.020 – 6 J                               |
| Laser frequency            | Up to 2,500 Hz                            |
| Average output             | Max. 60 W                                 |
| Pulse duration             | 50 μs – CW                                |
| Smallest fiber             | 150 μm                                    |
| Electrical requirements    | 100 – 240 Vac; 50/60 Hz; 1,000 VA         |
| Max. operating temperature | 10 – 30 °C                                |
| Pilot beam                 | Green, output can be adjusted             |
| Device design              | Tower with castors                        |
| Dimensions W x H x D       | 47,0 x 94,0 x 81,0 cm<br>(display closed) |
| Weight                     | 100 kg                                    |
| Laser cooling system       | Air                                       |

DANGER - Visible and invisible laser radiation. Avoid eye or skin exposure to direct or scattered radiation Class 4 laser product / Class 3R aiming beam

Distributed by R. WOLF

Richard Wolf GmbH Tel: +49 7043 35-0 Co-CFOs: Trade Register: Mannheim HRB 510031 Fax: +49 7043 35-4300 Jürgen Pfab VAT no.: DE144521586 info@richard-wolf.com Jürgen Steinbeck Tax no.: 48020/00171

